



















All leaks resulting during the application of **Navigator SC Termiticide/Insecticide** in locations other than those prescribed on this label must be cleaned up before leaving the application site. **DO NOT** allow people or pets to come in contact with contaminated areas until the cleanup is completed.

**Not for use in voids insulated with rigid foam.**

### Treatment of Structures with Wells or Cisterns

**DO NOT** contaminate wells or cisterns.

**DO NOT** apply **Navigator SC Termiticide/Insecticide** within 5 feet of any well or cistern. Treat soil 5 to 10 feet of any well or cistern by backfill method only. Treat soil adjacent to water pipes within 3 feet of grade by backfill method.

#### Backfill Method

- Trench to remove the soil to be treated and place it into a wheelbarrow or onto heavy plastic sheeting or similar material.
- Treat the soil at a rate of 4 gallons of finished dilution of **Navigator SC Termiticide/Insecticide** per 10 linear feet per foot of trench depth or at a rate of 1 gallon per cubic foot of soil. Mix the **Navigator SC Termiticide/Insecticide** thoroughly into soil while taking care to prevent runoff or spillage.
- After the treated soil has completely absorbed the finished dilution of **Navigator SC Termiticide/Insecticide** return the soil into the trench.

#### Structures Adjacent to Wells/Cisterns and/or Other Bodies of Water

Prior to application examine any structure with nearby sources of water such as wells, cisterns, ponds, streams or other bodies of water, then follow the treatment procedures described below:

- If the pipe(s) from the well enter the structure within 5 feet of grade expose them if possible prior to treatment. If feasible prior to treatment, expose the water pipe(s) coming from the well to the structure. Treat the soil adjacent to the water pipe(s) using the backfill method described above.
- Take precautions prior to treatment to limit the risk of **Navigator SC Termiticide/Insecticide** being applied to subsurface drains which empty into any bodies of water including evaluating whether treatment of the footer could result in contamination of subsurface drains. Take into consideration such factors as depth to the drain system, soil type and degree of compaction when determining the depth of treatment.
- Use the treated backfill method when applied to (for example on the water side of the structure) to minimize off site movement of **Navigator SC Termiticide/Insecticide**.
- To minimize potential runoff of **Navigator SC Termiticide/Insecticide** into non-target areas apply a finished dilution of 0.125% (rate of 2 gallons per 10 linear feet per foot of depth).

#### Plenum Construction

Before treatment turn off any air circulation equipment that moves air from the area to be treated to any untreated interior space of the structure. **DO NOT** turn the air circulation system back on until the application of **Navigator SC Termiticide/Insecticide** is completed and has been absorbed into the soil. Treat the soil exterior to the foundation walls according to the instructions in the *Accessible Crawl Space Construction* section of this label.

Follow the instructions below for interior treatment of plenum structures that use a sealed space to circulate heated or cooled air throughout the structure.

- Remove sealing fabric and anything on the sealing fabric to expose no more than 18 inches width adjacent to all foundation structures, including foundation walls, interior piers, pipes and any other structures in contact with soil. Treat according to the instructions for exterior and interior treatment in the *Accessible Crawl Space Construction* section of this label.
- After the finished dilution of **Navigator SC Termiticide/Insecticide** has been absorbed into the soil return the sealing fabric and anything removed from the surface of the sealing fabric to their original pre-treatment positions.

#### Foam Application

When construction practices, soil subsidence or other factors make it difficult to establish a continuous treated zone with conventional liquid application methods; supplement treatment with the use of foam generating equipment. Foam applications are useful in the treatment of filled stoops and porches, chimney bases, into block voids behind masonry or other veneers and into stud walls. Utilize applications of dry foam only (a range of 15:1 to 50:1

expansion ratio) when treating wall voids in stud walls. Apply foam to wall voids where evidence of termite presence or damage exist or are suspected. Foam only treatments under slabs are appropriate when maximum horizontal coverage is desired in areas with no deep foundation or footing (for example around plumbing entries and near settlement cracks in concrete slabs). Use both conventional liquid application and foam treatment in areas where both lateral spread and deeper vertical penetration of **Navigator SC Termiticide/Insecticide** are desired. Effective treatment is highly dependent on volume and amount of active ingredient. Apply at least 75% of the finished dilution of **Navigator SC Termiticide/Insecticide** as a liquid treatment then deliver the remaining 25% or less to the appropriate areas as a foam application. The total amount of product applied as a combined foam and liquid treatment should be equivalent to volume of **Navigator SC Termiticide/Insecticide** liquid finished dilution required for a liquid application alone. Foam applications provide a good supplement to liquid applications in difficult to treat areas

### Foam Mixing Instructions

Prepare the desired finished dilution of **Navigator SC Termiticide/Insecticide** then mix with the manufacturer's recommended quantity of foaming agent in suitable foaming equipment. Apply a sufficient volume of **Navigator SC Termiticide/Insecticide** foam to establish a continuous treated zone at the rates recommended in this label for specific applications. When sufficient foam volume cannot be applied to achieve the recommended rate of **Navigator SC Termiticide/Insecticide** supplement the treatment with additional liquid finished dilution to assure appropriate treatment volume and concentration in the treated area.

### Foam Application Rate Chart

- 1 gallon of finished dilution at a foam expansion ratio of 25:1 makes 25 gallons of foam.
- 1.66 gallons of finished dilution at a foam expansion ratio of 15:1 makes 25 gallons of foam.
- 2.5 gallons of finished dilution at a foam expansion ratio of 10:1 makes 25 gallons of foam.
- 5 gallons of finished dilution at a foam expansion ratio of 5:1 makes 25 gallons of foam.

## POST-CONSTRUCTION EXTERIOR PERIMETER/LOCALIZED INTERIOR (EP/LI) STRUCTURAL TERMITE TREATMENT

**Not Approved for Use in Louisiana**

### Post-Construction Exterior Application Information

Post construction application of **Navigator SC Termiticide/Insecticide** can be made after the final grade is installed to protect the structure from termite infestation and/or to control existing termite populations. This treatment method is designed to be non-invasive to the interior of the structure with the establishment of a continuous treated zone along the exterior of the foundation and only treating interior spaces where termite activity has been found. If you have questions regarding this treatment consult the appropriate state agency.

Termite activity is defined as the presence of one or more of the following signs of infestation:

- 1) Alates (winged termites) have swarmed inside the structure.
- 2) Live termites are found to be active within the structure.
- 3) There is clear evidence of termite activity on or inside the structure such as the presence of mud tubes galleries in wood and live termites.

**DO NOT** apply **Navigator SC Termiticide/Insecticide** finished dilution as perimeter/localized interior treatment at a concentration lower than 0.06% or at an application volume lower than those specified In the Application Rates for Termiticide Use section of this label.

### Exterior Perimeter Treatment

To prevent termite infestation of a structure using this treatment method, exterior perimeter applications of **Navigator SC Termiticide/Insecticide** must be made in a manner which will create a continuous treated zone. If situations are encountered where the soil will not accept the full application volume recommended in the use directions below, read and follow the directions in the *APPLICATION VOLUME FOR TERMITICIDE USE* section of this label.

### Concrete Slab on Ground (Including Monolithic Floating and Supported Concrete Slabs)

Apply along the exterior foundation perimeter by trenching and rodding into the trench or by trenching along the foundation walls at the rate of 4 gallons of finished dilution per 10 linear feet per foot of depth. Trenches need not be wider than 6 inches and must be a minimum of 6 inches deep or to the bottom of the footing. Space the rod holes no more than 12 inches apart in a manner which will create a continuous treated zone. Mix the finished dilution into the soil as it is replaced it into the trench. In areas where physical obstructions exist that prevent trenching such as concrete walkways adjacent to the foundation apply by rodding alone. Where soil type and/or conditions make trenching impossible apply by rodding. In order to establish a continuous exterior perimeter treatment zone, drilling

and sub-slab treatment will be necessary wherever adjoining concrete structures exist, such as, patios porches or sidewalks. For driveways, exterior drilling is necessary only around building supports or wall elements permanently located at driveway joints. Never treat a structure below the footing.

### **Basement and Inaccessible Crawl Space Construction**

Apply along the exterior foundation perimeter by trenching and rodding into the trench or by trenching along the foundation walls at the rate of 4 gallons of finished dilution of **Navigator SC Termiticide/Insecticide** per 10 linear feet per foot of depth or if the footing is more than 4 feet below grade, treat to a minimum depth of 4 feet. Trenches need not be wider than 6 inches and must be a minimum of 6 inches deep or to the bottom of the footing. When trenching in sloping or tiered soil, the trench must be stepped to ensure adequate distribution and to prevent **Navigator SC Termiticide/Insecticide** from running out of the trench. Space the rod holes no more than 12 inches apart in a manner which will create a continuous treated zone. Mix the finished dilution into the soil before replacing the soil into the trench. Never treat a structure below the footing. In areas where physical obstructions exist that prevent trenching, such as concrete walkways adjacent to the foundation, apply by rodding alone. Where soil type and/or conditions make trenching impossible, apply by rodding. In order to establish a complete exterior perimeter treatment zone, drilling and sub-slab treatment will be necessary wherever adjoining concrete structures exist, such as patios, porches or sidewalks. For driveways exterior drilling is necessary only around building supports or wall elements permanently located at driveway joints. Never treat a structure below the footing. If termite activity is detected inside an inaccessible crawl space the area must be treated. Make a localized interior treatment at the site of termite activity and extending at least 2 feet in both directions from the activity. Choose the appropriate application method for treating inaccessible crawl space construction by referring to the *POST CONSTRUCTION CONVENTIONAL STRUCTURAL TERMITE TREATMENT* section of this label.

### **Accessible Crawl Spaces**

**Before treatment turn off any air circulation equipment that moves air from the area to be treated to any untreated interior space of the structure. DO NOT turn the air circulation system back on until the application of Navigator SC Termiticide/Insecticide is completed and has been absorbed into the soil.** Treat crawl spaces by applying a vertical **Navigator SC Termiticide/Insecticide** treatment at the rate of 4 gallons of finished dilution per 10 linear feet per foot of depth from grade to the top of the footing or if the footing is more than 4 feet below grade, treat to a minimum depth of 4 feet. Apply by trenching and rodding into the trench or by trenching. Treat outside of the foundation and around all piers and pipes in area where physical obstructions exist that prevent trenching, such as concrete walkways adjacent to the foundation, apply by rodding alone. Where soil type and/or conditions make trenching impossible apply by rodding. When the top of the footing is exposed treat the soil adjacent to the footing to a depth not to exceed the bottom of the footing. In order to establish a complete exterior perimeter treatment zone drilling and sub-slab treatment will be necessary wherever adjoining concrete structures exist, such as patios, porches or sidewalks. If situations are encountered where the soil will not accept the full application volume recommended in the use directions below, read and follow the directions in the *Application Rates for Termiticide Use* section of this label.

- Rod holes and trenches must not extend beneath the bottom of the footing.
- Space the rod holes no more than 12 inches apart in a manner which will create a continuous treated zone.
- Trenches need not be wider than 6 inches and must be a minimum of 6 inches deep or to the bottom of the footing. When trenching in sloping or tiered soil the trench must be stepped to ensure adequate distribution and to prevent **Navigator SC Termiticide/Insecticide** from running out of the trench. Mix the finished dilution into the soil as it is replaced into the trench.

**Garages** - Attached garage floors should be treated.

**Sub-slab Injection:** Sub-slab injection treatments can be made from inside the garage or in cases where this is not possible from the outside of the structure by drilling through the foundation as directed below. Before treatment locate and identify all heating or air conditioning vents and ducts, water and sewer plumbing lines, electrical lines and conduits. Avoid contamination or damage to these structural elements.

**Vertical Drilling/Injection:** Make treatments under the slab by drilling vertically through the slab along the interior perimeter of the garage foundation. Drill holes along all concrete expansion joint cracks, plumbing and utility services penetrating the slab. Drill holes along interior partition walls when there is clear evidence of termite activity or damage. Space all drill holes no more than 12 inches apart in a manner which will create a continuous treated zone. Inject the finished dilution of **Navigator SC Termiticide/Insecticide** into the drill holes at a rate of 4 gallons per 10 linear feet per foot of depth. When making applications use a lateral dispersal nozzle to achieve the best results. After treatment, all holes in occupied areas must be plugged with a non-cellulose material or covered with an impervious non-cellulose material such as Portland cement.

**Horizontal Drilling/Rodding/Sub-slab Injection from the Exterior of the Garage Foundation:** Use this method to treat underneath the slab only when interior design does not allow for treatment by vertical drilling. Care must be taken not to rod into heating or air conditioning vents and ducts, water and sewer plumbing lines, electrical lines and conduits. Use a horizontal short rodding method to create a continuous treated zone along the inside perimeter of the foundation. Angle drill holes through the outside of the foundation to ensure deposition of **Navigator SC Termiticide/Insecticide** below any existing heating ducts, water and sewer lines or electrical conduits. Use a horizontal long rodding method only when the areas to be treated underneath the slab are not accessible by vertical rodding or horizontal short rodding. **DO NOT** use long rods exceeding 20 feet. For all horizontal rodding applications space drill holes no more than 12 inches apart in a manner which will create a continuous treated zone. Inject the finished dilution of **Navigator SC Termiticide/Insecticide** into the drill holes at rate of 4 gallons per 10 linear feet per foot of depth. All holes in occupied areas must be plugged with a non-cellulose material or covered by an impervious non-cellulose material such as Portland cement.

### **Localized Interior Treatment**

As part of a complete EP/LI treatment, targeted interior applications may be made to vulnerable areas such as around plumbing or utility services penetrating floors bath and/or shower traps or along concrete expansion joints or settlement cracks

If known termite activity exists in areas inside living spaces or in non-living spaces (such as crawl spaces, plenums, etc.) of the structure, a localized interior treatment must be made at the immediate vicinity of the termite activity and radiating out at least 2 feet from the site in two or more directions.

**Hollow Block Foundations / Voids:** When termite activity is evident in the vicinity (within 2 feet) of hollow block foundation or voids in masonry resting on the footing, drill the wall adjacent to the evidence if not openly accessible and inject the finished dilution of **Navigator SC Termiticide/Insecticide** into the void at a rate of 2 gallons per 10 linear feet of footing using a nozzle of 25 psi or less. This localized interior treatment to hollow block must be made to the site of the termite activity and to areas above the termite activity. Treatment must be applied radiating out at least 2 feet in two or more directions from the site of activity or along the wall or around the pier or support post. Use of foam will maximize dispersion. When using this treatment drill access hole below the sill plate as close as possible to the footing as is practical. Applicators must examine the treated areas of voids in block or rubble foundation walls closely for possible runoff as a precaution against application leakage. Mechanical alteration to some areas may be required before a treatment can be made. Some areas may not be treatable. All leaks resulting during the application of **Navigator SC Termiticide/Insecticide** in locations other than those prescribed on this label must be cleaned up before leaving the application site. **DO NOT** allow people or pets to come in contact with contaminated areas or allow them to reoccupy the treatment site until the cleanup is completed.

The drilled holes in occupied areas must be plugged with a non-cellulose material or covered by an impervious non-cellulose material such as Portland cement.

**Bath Traps:** If termite activity is evident within 2 feet of a bath trap, exposed soil or soil covered with tar or a similar sealant around plumbing and/or drain pipe entry areas must be treated. Tar or sealant may have to be removed to ensure adequate soil penetration. Install an access door or inspection portal if one is not already present. After all wood and cellulose debris is removed treat the soil by rodding or drenching with a minimum of 1 gallon to a maximum of 4 gallons of finished dilution of **Navigator SC Termiticide/Insecticide** per square foot.

**Shower Drains:** If termite activity is evident within 2 feet of a shower drain, soil beneath and adjacent to the drain must be treated. Drill through the slab adjacent to the shower drain and apply the finished dilution of **Navigator SC Termiticide/Insecticide** by sub-slab injection to the soil below. Multiple access points may be drilled adjacent to the drain. Use of foam will maximize dispersion. Use of a directional dispersion tip will further enhance the treatment of the soil beneath the drain. Treat the soil with a minimum of 1 gallon but no more than 4 gallons of finished dilution per shower drain. Horizontal rodding can also be used to access and treat soil associated with the shower drain.

## RETREATMENT INSTRUCTIONS

**Annual retreatment of a structure is prohibited.** Retreatment for subterranean termites can only be performed under the following circumstances:

- There is clear evidence of reinfestation.
- There is disruption of the treated zone due to construction excavation or landscaping and/or there is evidence of the breakdown of the termiticide treated zone in the soil.

Treat these vulnerable or reinfested areas using a spot, partial or complete treatment in accordance with the application techniques described in this label. The timing and selection of retreatment type will vary depending on such factors as termite pressure, soil types and conditions and other factors which may reduce the effectiveness of the treated zone.

### POSTS, POLES, WOOD LANDSCAPE ORNAMENTATION

**DO NOT contaminate wells or cisterns.**

**Preventative Treatment:** Create a continuous treatment zone in the soil around wooden posts, poles, fence posts, signs, and landscaping ornamentation. Apply the finished dilution of **Navigator SC Termiticide/Insecticide** at the rate of 4 gallons per 10 linear feet per foot of depth. When performing the treatment at the time of installation, the finished dilution may be applied to the soil as it is replaced around the pole or post. The application should place termiticide to a depth of 6 inches below the bottom of posts, poles or other wooden objects in contact with soil.

**Curative Treatment:** Treat previously installed wooden posts, poles, fence posts, signs, and landscaping ornamentation with the finished dilution of **Navigator SC Termiticide/Insecticide** by sub-surface injection, or by gravity flow through holes made at the bottom of a trench around posts and poles. When trenching, the trench need not be wider than 6 inches and should be 6 inches deep. When sub-surface injecting, treat all sides to create a continuous treatment zone. Apply termiticide to a depth of 6 inches below the bottom of the wood.

### TERMITES ABOVE GROUND

**For Control of Termite Above Ground Colonies or Drywood Termites:** To treat localized areas of wooden structures, apply the finished dilution of **Navigator SC Termiticide/Insecticide** to wooden members / voids. To treat inaccessible areas drill and inject the finished dilution into any void spaces in the damaged wood with a crack and crevice injector. Foam application can also be made into void spaces. To treat termite carton nests in trees or building voids, inject the finished dilution of **Navigator SC Termiticide/Insecticide** using a pointed injection tool. Multiple injection points to varying depths may be necessary. Physically remove carton nest material from building voids when such nests are found. After treatment the applicator is required to check for leaks resulting in the deposition of **Navigator SC Termiticide/Insecticide** in locations other than those prescribed on this label. When and if found, this material must be cleaned up before leaving the application site. **DO NOT** allow people or pets to come in contact with contaminated areas or allow them to reoccupy the treatment site until the cleanup is completed.

**DO NOT TREAT FRUIT OR NUT BEARING TREES**

### DIRECTIONS FOR USE TO CONTROL LISTED PESTS ON OUTSIDE SURFACES AND ALONG FOUNDATION PERIMETER OF LISTED STRUCTURES

Listed structures are residential, institutional, commercial and industrial buildings and utility enclosures.

#### USE RESTRICTIONS

- Only applicators wearing the personal protective equipment required by this product label may be in the area during application.
- **DO NOT** treat within a distance of 1 foot out from the drip line of edible plants.
- **DO NOT** contaminate public or private water supplies.
- **DO NOT** contaminate water, food, or feed. Cover or remove all exposed food, feed, and drinking water.
- **DO NOT** use in tanks with borate contaminants.
- **DO NOT** apply to wasp or hornet nests if they are not attached to the structure exterior or inside wall voids.
- **DO NOT** make treatments during times of precipitation.
- **DO NOT** allow resident's children, other people or pets into the treatment area until sprays have dried. After treatment the applicator is required to check for leaks resulting in the deposition of

treatment dilution in locations other than those prescribed in this label. When found, this material must be cleaned prior to leaving the application site.

- **DO NOT** allow people or pets to contact contaminated areas or to reoccupy contaminated areas of the structure until cleanup is completed.
- **DO NOT** spray air conditioning units or intake vents.
- **DO NOT** use indoors except for application into wall voids.
- **DO NOT** apply to playground equipment or pet quarters.
- **DO NOT** apply to the point of runoff or drip from treated surfaces.
- **DO NOT** apply to boat houses including their piers or pilings.
- **DO NOT** apply within 5 feet of wells or cisterns.
- **DO NOT** apply to French drains or other permeable drainage.
- Doors and windows adjacent to application site must be closed during surface application.
- **DO NOT** apply within 15 feet of bodies of fresh water lakes, reservoirs, rivers, permanent streams, marshes, natural ponds, and commercial fish ponds. A 15 foot buffer of uniform ground cover must exist between application zone and bodies of fresh water (Uniform ground cover is defined as land which supports vegetation of greater than 2 inches in height throughout).
- **DO NOT** apply within 60 feet of estuarine bodies of water. Estuarine water bodies are brackish tidal water bodies, such as, bays, mouths of rivers, salt marshes, and lagoons.

**CALIFORNIA USE RESTRICTIONS:** In addition to use restrictions stated above, applications made in California are subject to the following additional restrictions.

- **DO NOT** apply **Navigator SC Termiticide/Insecticide** to the garage door, driveway, vertical surfaces above the driveway and garage door, or to cracks and crevices leading or adjacent to the driveway such as the expansion joint between the garage and driveway.
- **DO NOT** apply bandwidth at greater than 6 inches out and 6 inches up from where the ground meets the foundation.
- **ONLY** use 0.03% dilution mixing rate.
- **DO NOT** re-apply at intervals less than 60 days.
- **DO NOT** apply more than 4 times per year.
- **DO NOT** make applications on any date between November 1 and February 28.

**Use Navigator SC Termiticide/Insecticide to kill and to provide residual control of the following pests:**

Ants (acrobat, Argentine, big headed, carpenter, crazy, odorous pavement, pharaoh and thief)

**Use Navigator SC Termiticide/Insecticide to kill the following pests:**

Asian lady beetles  
Darkling beetles  
Australian, Oriental and smoky brown cockroaches  
Black widow, brown recluse, cellar and hobo spiders  
Box elder bugs  
Brown dog ticks  
Centipedes  
Cluster flies  
European earwigs  
House Crickets  
Millipedes  
Paper wasps\*  
Pill bugs  
Silverfish  
Yellow Jackets\*

**\*NOTE: Navigator SC Termiticide/Insecticide** is not a knockdown agent.

**Mixing Instructions\*:** For perimeter pest treatments fill the treatment tank 1/4 to 1/3 with water then add 0.8 fluid ounces (or 0.4 fluid ounces) of **Navigator SC Termiticide/Insecticide** to achieve 0.06% (or 0.03%) finished dilution rate. The filling hose must be equipped with an anti-backflow device or the water flow must include an air gap to protect against back siphoning. Add more water to the tank while agitating to make 1 gallon of finished dilution.

Permitted Navigator SC Frequency and Dilution Rate Application Scenarios <sup>†</sup>		
% Navigator SC Termiticide/Insecticide finished dilution		
0.03% 4 times/calendar year	0.06% 2 times/calendar year	0.03% 2 times/calendar year and 0.06% 1 time/calendar year
<sup>†</sup> In California, <b>ONLY</b> the 0.03% dilution may be applied at 1 quart per 160 ft.		

**\*CALIFORNIA MIXING INSTRUCTIONS:** For perimeter pest treatments, mix a 0.03% spray dilution of **Navigator SC Termiticide/Insecticide** by filling the treatment tank 1/4 to 1/3 full with water, then add 0.4 fluid ounces of **Navigator SC Termiticide/Insecticide**. The filling hose must be equipped with an anti-backflow device or the water flow must include an air gap to protect against back siphoning. Add more water to the tank while agitating to 1 gallon of finished dilution.

**Application Instructions to Outside Surfaces of Listed Structures and into Wall Voids:** For perimeter pest treatments mix and apply a finished spray dilution of **Navigator SC Termiticide/ Insecticide**. See the Mixing Instruction section of this label for instructions. Make applications using a low pressure spray to the exterior of the structure where listed pests enter and trail around the structure or where they crawl and hide. Treat using a low pressure coarse banded surface spray up to 18 inches in width around doors, windows, vents pipes, foundation cracks, and drilled holes or around any exterior openings where listed pests could enter the structure. Make sure to treat the joints where exterior siding (wood, vinyl, aluminum or other similar materials) meets the cement brick or block of the foundation. Treat areas where electrical cable or telephone wires enter the house. This treatment should be made as a general surface spray, crack and crevice spray or a wall void application. **Navigator SC Termiticide/Insecticide** may be applied as a foam treatment into wall voids to kill and/or control the above listed pests. Refer to the *FOAM APPLICATION* section of this label for specific foam mixing and application instructions.

**In California:** Use only the 0.03% finished dilution no more than 4 times per year. **DO NOT** apply to the garage door, driveway, vertical surfaces above the driveway and garage door, or to cracks and crevices leading or adjacent to the driveway, such as, the expansion joint between the garage and driveway. **DO NOT** apply a bandwidth greater than 6 inches up and out from where the ground meets the foundation.

**Applications to Perimeter of Listed Structures\*:** Apply a finished spray dilution of **Navigator SC Termiticide/Insecticide** as a low-pressure coarse general spray along the foundation exterior perimeter to an area one foot up and one foot out from where the ground meets the foundation. Apply 2 quarts of 0.06% finished spray dilution of **Navigator SC Termiticide/Insecticide** per 160 linear feet (approximately 1.5 gallons finished spray per 1000 sq feet). Nests that are found on the ground within 1 foot of the foundation may be treated. Vegetation touching the structure may offer a route for the entry of ants into the structure without coming into contact with the treatment, therefore remove or prune away any shrubbery, bushes and tree branches touching the structure.

**\*CALIFORNIA APPLICATIONS TO PERIMETER OF LISTED STRUCTURES:**

Apply 0.03% **Navigator SC Termiticide/Insecticide** finished dilution as a low pressure (25 PSI or less at the nozzle) coarse general surface spray along the foundation exterior perimeter to an area 6 inches up and 6 inches out from where the ground meets the foundation. **DO NOT** apply **Navigator SC Termiticide/Insecticide** to the garage door, driveway, vertical surfaces above the driveway and garage door, or to cracks and crevices leading or adjacent to the driveway, such as, the expansion joint between the garage and driveway.

In California, apply 1 quart of **Navigator SC Termiticide/Insecticide** finished dilution per 160 linear feet (approximately 1.5 gallons finished spray per 1000 square feet). Vegetation touching the structure may offer a route for the entry of ants into the structure without coming into contact with the treatment, therefore, remove or prune away any shrubbery, bushes and tree branches touching the structures.

## STORAGE AND DISPOSAL

**DO NOT** contaminate water, food, or feed by storage or disposal.

### PESTICIDE STORAGE

Unused product should be stored in its original container only, out of the reach of children and animals.

### PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**SPILLS:** For minor spills, leaks, etc., follow all precautions indicated on this label and clean up immediately. Soak up spilled material with sand, earth or other suitable material and dispose of as pesticide waste. Take special care to avoid contamination of equipment and facilities during cleanup procedures and disposal of wastes. Refer to Precautionary Statements on label for hazards associated with the handling of this material. **DO NOT** walk through spilled material. In spill or leak incidents, keep unauthorized people away. **You may contact the CHEMTREC Emergency Response for decontamination procedures.**

**For Chemical Spill, Leak, Fire, Exposure, or Accident you may call CHEMTREC at 1-800-424-9300 twenty-four (24) hours per day, seven (7) days per week.**

### CONTAINER HANDLING

**Nonrefillable Container. DO NOT reuse or refill this container.** Triple rinse or pressure rinse container (or equivalent) promptly after emptying; then offer for recycling, if available, or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or by incineration, or by other procedures approved by state and local authorities.

- **Triple rinse containers small enough to shake (capacity  $\leq$  5 gallons) as follows:** Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container  $\frac{1}{4}$  full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank, or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.
- **Pressure rinse as follows:** Empty the remaining contents into application equipment or mix tank. Hold container upside down over application equipment or mix tank, or collect rinsate for later use or disposal. Insert pressure rinsing nozzle in the side of the container and rinse at about 40 PSI for at least 30 seconds. Drain for 10 seconds after the flow begins to drip.



## **Conditions of Sale and Warranty Inherent Risks of Use**

It is impossible to eliminate all risks associated with use of this product. Lack of performance, or other unintended consequences may result because of such factors as use of the product contrary to label instructions (including conditions noted on the label, such as unfavorable temperatures, soil conditions, etc.), abnormal conditions (such as excessive rainfall, drought, tornadoes, hurricanes), presence of other materials, the manner of application, or other factors, all of which are beyond the control of Gharda Chemicals International, Inc. or the seller. To the extent permitted by applicable law, all such risks shall be assumed by buyer.

## **Notice of Warranty and Disclaimer**

Seller warrants that at the time of delivery the product in this container conforms to its chemical description contained hereon and is reasonably fit for its intended purpose under normal conditions of use. This is the only warranty made on this product. To the extent permitted by applicable law, Seller expressly disclaims any implied warranties of merchantability or fitness for any particular purpose and, except as set forth above, any other express or implied warranties. Any damages arising from breach of warranty or negligence shall be limited to direct damages not exceeding the purchase price paid for this product by Buyer, and shall not include incidental or consequential damages such as, but not limited to, loss of profits or values. It is impossible to eliminate all risks inherently associated with the use of this product. Ineffectiveness or other un-intended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application, all of which are beyond the control of the Seller. To the extent permitted by applicable law Seller be liable for the consequential, special or indirect damages resulting from the use or handling of this product. The Buyer shall assume all such risks. Buyer acknowledges the use of its own independent skill and expertise in the selection and use of the product and does not rely on any oral or written statements or representations.

**NAVIGATOR is a Registered Trademark of Gharda Chemicals International, Inc.**

**Teejet** is a registered trademark of Spraying Systems Co.

**Raindrop** is a registered trademark of Delavan Corporation

EPA Accepted: August 26, 2014

Amended (First Aid): 02/24/2017

Notification (Add Shake DFU Stmt): 03/18/2017

Amended (Add CA DFU): June 08, 2017

Notification (Rate Error): June 28, 2017

Manufactured for:

**Gharda Chemicals International, Inc.**

760 Newtown-Yardley Rd. Suite 110

Newtown, PA 18940

1-215-968-9474